

Datum: 16.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Spir. cev , standard, PU, cevi Ø 12x8, dolžina 10 m

Kategorija: [Spiral hose coupling kit quick disconnect coupling](#)
Šifra: **158185RIE**

Kratek opis

Spiral hose coupling set, Standard coupling I.D. 7.2, PU, Hose Ø 12x8, PN at 23 °C max. 10 bar, Length 10.0 m
These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional polyamide spiral hose, but with less tendency to loop and significantly better resistance to abrasion.
There is consequently less danger of scratching coated or sensitive surfaces.
The hose is extremely flexible and non-kinking.
Not suitable for direct attachment to pulsating tools.
We recommend using our vibration dampers, according to ISO 6150 § 7.1.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Max. obratovalni tlak pri 23 ° C [bar]	10
Storitev dolžina max. [m]	10.0
Velikost cevi [mm]	12x8
Število tuljav	54
Max. delovna temperatura [°C]	60
O.D. tuljave [mm]	82