

Datum: 14.05.2024



(slika je simbolična)

## Spojka s cevni nastavkom I.D. 7.8SEK tip, poniklj. Med.I.D. 9

Kategorija: [Safety coupling DN 7.8, with hose stem](#)Šifra: **107538RIE**

### Kratek opis

Safety coupling I.D. 7.8, SEK type, nickel-plated brass, Sleeve I.D. 9, Operating pressure 0 - 35 bar, Temp. -10 °C to 60 °C

One-hand safety coupling with double locking mechanism. Connection: Similar to standard couplings, simply by pressing the plug into the coupling. Disconnection: The first locking mechanism is accessible when the sleeve is pushed back. The coupling valve closes. Air can then be relieved from the plug side (hose). The second locking mechanism is released by actuating the unlocking sleeve again. The coupling can now be disconnected.

### Tehnične Specifikacije

|                              |                                                              |
|------------------------------|--------------------------------------------------------------|
| Min. sobna temperatura [°C]  | -10                                                          |
| Min. temperatura medija [°C] | -10                                                          |
| Delovni tlak                 | 0 to 35 bar, maximum static working pressure (non-pulsating) |
| Krogla                       | Stainless steel                                              |
| Merjenje pretoka             | at 6 bar and $\Delta p = 0.5$ bar                            |
| Ohišje                       | Nickel-plated brass                                          |
| Povezava                     | I.D. 9                                                       |
| Rokav                        | Nickel-plated brass                                          |
| Telo ventila                 | Nickel-plated brass                                          |
| Tesnilo                      | NBR                                                          |
| Vzmet                        | Stainless steel                                              |
| DN                           | 7.8                                                          |
| a/f [mm]                     | 22                                                           |
| Dolžina [mm]                 | 60.0                                                         |
| Max. sobna temperatura [°C]  | 60                                                           |
| Max. temperatura medija [°C] | 60                                                           |
| Pretok                       | 1100 l/min (air)                                             |