



(slika je simbolična)

## **Standardni manometer, priklup spodaj, G 1/2, 0 - 40 bar, Ø 160**

Kategorija: [Wika](#)  
Šifra: **101996RIE**

### **Kratek opis**

Standard pressure gauge, Single scale bar, Connection radial bottom, G 1/2, Goods class 1.6, Measurement range 0 - 40 bar, Ø 160  
Bourdon-tube pressure gauge in standard design.  
Suitable for gaseous or liquid media which do not corrode copper alloy,  
do not have high viscosity and do not crystallise.

### **Tehnične Specifikacije**

|                                            |                       |
|--------------------------------------------|-----------------------|
| Min. sobna temperatura [°C]                | -20                   |
| Min. temperatura medija [°C]               | -20                   |
| Material Prozessanschluss                  | Copper alloy          |
| Merilni element                            | Copper alloy          |
| Ohišje                                     | Sheet steel           |
| Položaj povezave                           | radial on bottom      |
| Povezava                                   | G 1/2                 |
| Prednje steklo                             | Flat instrument glass |
| Premikanje                                 | Copper alloy          |
| Referenčni kazalnik                        | red                   |
| Spodnja/Zgornja meja območja               | Positive pressure     |
| Stopnja rasti na območju skale - bar [bar] | 1                     |
| Razred točnosti                            | 1.6                   |
| Merilno območje max. bar                   | 40                    |
| Max. sobna temperatura [°C]                | 60                    |
| Max. temperatura medija [°C]               | 60                    |
| Vrsta                                      | 111.10                |
| Premer [mm]                                | 160                   |