



Standardni manometer, trikoten sprednji obroč, G 1/8, 0 - 1 bar

Kategorija: [Wika](#)
Šifra: **101912RIE**

(slika je simbolična)

Kratek opis

Standard pressure gauge, triangle front ring, Connection, rear, centric, G 1/8, Goods class 2.5, Measurement range 0 - 1 bar, Ø 40
Bourdon-tube pressure gauge in standard design, either with panel-mounting bezel made of chrome-plated or black sheet steel or with 3-hole bezel made of chrome-plated sheet steel. Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Material Prozessanschluss	Copper alloy
Merilni element	Copper alloy
Ohišje	Sheet steel
Položaj povezave	rear, central
Povezava	G 1/8
Prednje steklo	Transparent plastic
Premikanje	Copper alloy
Spodnja/Zgornja meja območja	Positive pressure
Stopnja rasti na območju skale - bar [bar]	0.05
Merilno območje max. bar	1
Razred točnosti	2.5
Merilno območje max. psi	14.5
Premier [mm]	40
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Vrsta	111.12