

Datum: 15.05.2024



(slika je simbolična)

## Tlačni regulator »Stinard-mali«, G 1/4, 0.5 - 10 bar

Kategorija: [Pressure regulators, independent of inlet pressure](#)Šifra: **100778RIE**

### Kratek opis

Pressure regulator »Standard-mini«, incl. pressure gauge and control panel nut, G 1/4, Input pressure max. 25 bar, 0.5 - 10 bar

Compact, reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design. The pressure setting can be locked by pushing the knob down.

### Tehnične Specifikacije

|                              |                                                                      |
|------------------------------|----------------------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                        | G 1/4                                                                |
| Ohišje                       | Die-cast zinc, painted silver                                        |
| Serija                       | Standard-mini                                                        |
| Tesnilo                      | NBR                                                                  |
| Vzmet pokrova motorja        | POM-brass                                                            |
| Min. krmilno območje [bar]   | 0.5                                                                  |
| DN                           | 5                                                                    |
| Max. krmilno območje [bar]   | 10                                                                   |
| C [mm]                       | 15.0                                                                 |
| Zaslon manometra max. [bar]  | 16                                                                   |
| Max. vhodni tlak [bar]       | 25                                                                   |
| A [mm]                       | 40.0                                                                 |
| Max. sobna temperatura [°C]  | 60                                                                   |
| Max. temperatura medija [°C] | 60                                                                   |
| D [mm]                       | 61.3                                                                 |
| B [mm]                       | 76.3                                                                 |
| Pretok [l/min]               | 330                                                                  |