

Datum: 15.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Varnostni krogelni ventil, z zaklepom, brez izpustom, Rp 3/4

Kategorija: [Safety ball valves, lockable, without relief port](#)
Šifra: **103144RIE**

Kratek opis

Safety ball valve, lockable, without venting hole, nickel-plated brass, Operating temp. max. 170°C, Rp 3/4, DN 20, PN max. 65 bar
2/2-way safety ball valves made of nickel-plated brass.
The ball valve can be locked manually.
Full bore, heavy-duty type.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-40
Bore diameter padlock	ca. 7.4 mm
Krogelno tesnilo	PTFE
Material	Nickel-plated brass
Material navojev	Nickel-plated brass
Navoj	Rp 3/4
Ročica	Steel - PVC coated
Standardni navoj	Rp thread acc. to EN 10226
Stebelno tesnilo	PTFE
DN	20
B [mm]	52.5
PN [bar]	65
L [mm]	74.5
A [mm]	120.0
Max. delovna temperatura [°C]	170