

Datum: 16.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Visoko zmogl. varnos.ventil, G 2, vkl. prit. 18 bar

Kategorija: [High-pressure Varnostni ventil G 2](#)  
Šifra: **105427RIE**

### Kratek opis

High performance safety valve, Vibration-proof design, Brass, Operating temp. max. 260 °C, G 2, AF 80, Trigger pressure 18 bar  
Proportional, spring-loaded safety valves with a lifting device. Type-tested acc. to VdTÜV Specification for safety valves 100.  
Exceptionally reliable, even when installed in extreme environments (vibration-resistant design).  
Suitable for compressed air and other non-toxic, neutral and non-flammable gases that may be freely released. Not suitable for steam.

### Tehnične Specifikacije

|                               |                                    |
|-------------------------------|------------------------------------|
| Navoj                         | G 2                                |
| Ohišje                        | Brass                              |
| Vzmet pokrova motorja         | Malleable iron, powder-coated blue |
| Min. obratovalni tlak [bar]   | 0.5                                |
| Min. nastavljeni tlak [bar]   | 18                                 |
| A [mm]                        | 22.0                               |
| Max. obratovalni tlak [bar]   | 30                                 |
| narediti [mm]                 | 40.0                               |
| a/f [mm]                      | 80                                 |
| Max. delovna temperatura [°C] | 260                                |
| H [mm]                        | 367.0                              |