

Datum: 15.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



Vklopni ventil »multifix« z nastavljivim gumbom Vel.1,G 1/4

Kategorija: [Start-up valves](#)
Šifra: **100626RIE**

(slika je simbolična)

Kratek opis

Start up valve »multifix«, with adjustable throttle, Size 1, G 1/4, Input pressure 2 - 16 bar, Medium / ambient temp. max. 60 °C

Seat valves operated by secondary pressure for controlled pressurisation of pneumatic systems.

The full cross-section of the regulator is opened at 50% of the input pressure.

The filling time can be altered by turning the adjusting screw.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/4
Ohišje	Die-cast zinc
Serijska	multifix
Tesnilo	NBR
Velikost	1
Min. vhodni tlak [bar]	2
Max. vhodni tlak [bar]	16
D [mm]	26.8
A [mm]	47.8
B [mm]	54.2
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Pretok [l/min]	1100