

Datum: 23.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Hitre spojke I.D. 5, zunanji navoj medenina, cev I.D. 6

Kategorija: [Quick disconnect coupling DN 5, with hose stem](#)  
Šifra: **107133RIE**

### Kratek opis

Quick-connect coupling I.D. 5, bright brass, Sleeve I.D. 6,  
Operating pressure 0 - 35 bar, Medium / ambient temp. -20  
°C to 100 °C

"

One-hand quick disconnect couplings, one side sealing,  
compact with a large bore and only a small pressure drop.  
To prevent injuries or a "whiplash" effect, we recommend  
that the plug-in nipple is held with one hand during  
uncoupling.

Areas of application: Pneumatic system, measurement,  
monitoring and control systems, manufacturing industry,  
medical technology, chemical / pharmaceutical industry,  
automotive, food technology.

"

### Tehnične Specifikacije

|                                 |                                                                    |
|---------------------------------|--------------------------------------------------------------------|
| Min. sobna<br>temperatura [°C]  | -20                                                                |
| Min. temperatura<br>medija [°C] | -20                                                                |
| Delovni tlak                    | 0 to 35 bar, maximum<br>static working pressure<br>(non-pulsating) |
| Krogla                          | Stainless steel                                                    |
| Merjenje pretoka                | at 6 bar and $\Delta p = 0.5$ bar                                  |
| Ohišje                          | Brass with a bare metal<br>surface                                 |
| Povezava                        | I.D. 6                                                             |
| Pritrdilni obroč                | Stainless steel                                                    |
| Rokav                           | Brass with a bare metal<br>surface                                 |
| Telo ventila                    | Brass with a bare metal<br>surface                                 |
| Tesnilo                         | NBR                                                                |
| Vzmet                           | Stainless steel                                                    |
| DN                              | 5                                                                  |
| Dolžina [mm]                    | 46.0                                                               |
| Max. sobna<br>temperatura [°C]  | 100                                                                |
| Max. temperatura<br>medija [°C] | 100                                                                |
| Pretok                          | 560 l/min (air)                                                    |