



(slika je simbolična)

Priključek, 3 vrtlj. spojke I.D.7.2

Kategorija: [Distributor socket with swing safety couplings DN 7.2](#)
Šifra: **142180RIE**

Kratek opis

End distributor socket, 3 swing safety couplings, I.D. 7.2, input G 1/2, Operat. pressure max. 12bar, Ambient temp. -10°C to 50°C2 or 3-way distributor sockets made of high-strength glass fibre-reinforced plastic (PA6 GF 30) for a wide range of applications. Available with 2 or 3 pre-assembled, swing safety couplings and 2 inlet thread sizes for input and output threads (Not combinable). All distributor sockets have a durable brass threaded insert, whose shape secures it against rotation and against axial shift due to its shape. Drilling diagram dimensions are identical for all distributor sockets, so a simpler and more flexible exchange replacement. Caution: Note that the distributor sockets should not be installed in danges zones. Danger zones are, for example, transport routes, escape routes, etc.

Tehnične Specifikacije

Dovodni navoj	G 1/2
Material navojev	Brass
Ohišje	Glass fibre-reinforced plastic
Spojka	3 x swing safety coupling
Max. moment privijanja - pritrdilne luknje [Nm]	4
Max. moment privijanja - medeninasta nit [Nm]	12
Max. obratovalni tlak [bar]	12
Višina [mm]	59.0
Premer [mm]	165.0